



GROWING TOGETHER

XL GRIP



- The XL GRIP is a bias ply tire for Tipper application it is engineered & designed to minimize cut & punctures in rocky mining environments, where exceptional traction is required



XL GRIP



GROWING TOGETHER

Tough non-directional tread pattern for mounting versatility & excellent traction on rocky surfaces

Centre tie-bar for excellent stability

Self-cleaning tread design



Strong casing & cut resistant tread compound for excellent cut /chip resistant & durability

Squared shoulder maximizes ground contact for excellent maneuverability & handling

Tire Size	Pattern	TRA Code	Type	Rim		Unloaded inflated Dimensions $\pm 2.5\%$		Static Loaded Radius (mm)	Rolling Circumference $\pm 2.5\%$ (mm)	NSD (mm)	Ply Rating	LOAD DATA		
				Rec.	Alt.	Overall Width (mm)	Overall Diameter (mm)					SPEED (kmph)	LOAD (kgs)	PRESSURE (bar)
10.00-20	XL GRIP	--	TT	7.5	7	285	1075	505	3257	22	18	90*	2800	7.6
11.00-20	XL GRIP	--	TT	8.0	7.5	297	1115	529	3368	25	18	90*	3000	7.6
12.00-20	XL GRIP	--	TT	8.5	8.0	320	1155	545	3465	24	20	90*	3550	7.9
12.00-24	XL GRIP	--	TT	8.5	8	320	1250	585	3710	24	20	80*	3875	7.9

* Distance must not exceed 90km in any 1.5 hour period of run

RELEASE DATE JULY 2015

